



DS30 RECEPTACLE

33-34143-375-843

SPECIFICATIONS

30 A
 600 VAC
 Type 3R
 15 hp

| | |
|---|---|
| Rated Current (A) | 30 A |
| Rated Voltage (V) | 600 VAC |
| Horsepower Rating | 15 hp |
| Contact Configuration | 3P+G |
| Auxiliary Contacts | NO AUX |
| Ratings Information | SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH |
| Environmental Rating | Type 3R IP 55 |
| Short Circuit Rating | 100 kA - CLOSE & WITHSTAND |
| Impact Rating | IK09 |
| Material | POLY |
| Product Color | BLUE |
| Minimum Operating Temperature | -40F -40C |
| Maximum Operating Temperature | 140F 60C |
| Wiring Capacity - Phase Contacts | 14 AWG - 4 AWG SCREW TERMINAL |
| Applicable Standards | UL 2682 UL 1682 cCSAus C22.2 No. 182.1-13 |
| Option(1) | PADLOCKABLE MUSHROOM PAWL |
| Accessory Size | 3 |
| Base Drawing Number | 33-34xxx.PDF |
| Catalog | meltric-catalog-ds30-en.pdf |