



# DS30 INLET

33-38143-973-4X

## SPECIFICATIONS

30 A  
 600 VAC  
 Type 4X  
 15 hp

|                                         |                                                                                     |
|-----------------------------------------|-------------------------------------------------------------------------------------|
| <b>Rated Current (A)</b>                | 30 A                                                                                |
| <b>Rated Voltage (V)</b>                | 600 VAC                                                                             |
| <b>Horsepower Rating</b>                | 15 hp                                                                               |
| <b>Contact Configuration</b>            | 3P+G                                                                                |
| <b>Auxiliary Contacts</b>               | +3 AUX                                                                              |
| <b>Ratings Information</b>              | SWITCH RATED<br>BRANCH CIRCUIT DISCONNECT SWITCH<br>MOTOR CIRCUIT DISCONNECT SWITCH |
| <b>Environmental Rating</b>             | Type 4X<br>IP 66/67                                                                 |
| <b>Short Circuit Rating</b>             | 100 kA - CLOSE & WITHSTAND                                                          |
| <b>Impact Rating</b>                    | IK09                                                                                |
| <b>Material</b>                         | POLY                                                                                |
| <b>Product Color</b>                    | BLUE                                                                                |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                                                        |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                                                                         |
| <b>Wiring Capacity - Phase Contacts</b> | 14 AWG - 4 AWG<br>SCREW TERMINAL                                                    |
| <b>Applicable Standards</b>             | UL 2682<br>UL 1682<br>cCSAus<br>C22.2 No. 182.1-13                                  |
| <b>Option(1)</b>                        | TYPE 4X WATERTIGHTNESS                                                              |
| <b>Accessory Size</b>                   | 3                                                                                   |
| <b>Base Drawing Number</b>              | <a href="#">33-38xxx.PDF</a>                                                        |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-ds30-en.pdf</a>                                         |