



DS60 RECEPTACLE

33-64047-972-843-NC

SPECIFICATIONS

60 A
 277/480 VAC
 Type 4X & IP69
 7.5 hp/25 hp

Rated Current (A)	60 A
Rated Voltage (V)	277/480 VAC
Horsepower Rating	7.5 hp/25 hp
Contact Configuration	3P+N+G
Auxiliary Contacts	+2 AUX
Ratings Information	SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH
Environmental Rating	Type 4X IP 66/67 IP 69
Short Circuit Rating	100 kA - CLOSE & WITHSTAND
Impact Rating	IK09
Material	POLY
Product Color	BLUE
Minimum Operating Temperature	-40F -40C
Maximum Operating Temperature	140F 60C
Wiring Capacity - Phase Contacts	10 AWG – 2 AWG SCREW TERMINAL
Applicable Standards	UL 2682 UL 1682 cCSAus C22.2 No. 182.1-13
Option(1)	PADLOCK PAWL
Option(2)	SELF-RETURNING LID
Accessory Size	4
Base Drawing Number	33-64xxx.PDF
Catalog	meltric-catalog-ds60-en.pdf