



# DSDC6 RECEPTACLE

33-64109

## SPECIFICATIONS

60 A

130 VDC

Type 4X & IP69

|   |   |
|---|---|
| <b>Rated Current (A)</b>                | 60 A  |
| <b>Rated Voltage (V)</b>                | 130 VDC                                     |
| <b>Contact Configuration</b>            | 2P+G  |
| <b>Ratings Information</b>              | NON-CURRENT INTERRUPTING                    |
| <b>Environmental Rating</b>             | Type 4X<br>IP 66/67<br>IP 69                |
| <b>Impact Rating</b>                    | IK09  |
| <b>Material</b>                         | POLY  |
| <b>Product Color</b>                    | BLUE  |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                                 |
| <b>Wiring Capacity - Phase Contacts</b> | 10 AWG – 2 AWG<br>SCREW TERMINAL            |
| <b>Applicable Standards</b>             | UL 1682<br>cCSAus<br>C22.2 No. 182.1-13     |
| <b>Accessory Size</b>                   | 4   |
| <b>Base Drawing Number</b>              | <a href="#">33-64xxx-xxx.pdf</a>            |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-dsdc-en.pdf</a> |