



# DS30 HAZ RECEPTACLE

35-34043-HAZ

## SPECIFICATIONS

30 A  
480 VAC  
Type 4X  
15 hp

|   |   |
|---|---|
| <b>Rated Current (A)</b>                | 30 A  |
| <b>Rated Voltage (V)</b>                | 480 VAC   |
| <b>Horsepower Rating</b>                | 15 hp   |
| <b>Contact Configuration</b>            | 3P+G  |
| <b>Auxiliary Contacts</b>               | NO AUX  |
| <b>Ratings Information</b>              | NON-CURRENT INTERRUPTING                          |
| <b>Environmental Rating</b>             | Type 4X   |
| <b>Short Circuit Rating</b>             | 100 kA - CLOSE & WITHSTAND                        |
| <b>Impact Rating</b>                    | IK09  |
| <b>Material</b>                         | POLY  |
| <b>Product Color</b>                    | BLACK   |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                      |
| <b>Maximum Operating Temperature</b>    | 104F<br>40C                                       |
| <b>Wiring Capacity - Phase Contacts</b> | 14 AWG - 4 AWG<br>SCREW TERMINAL                  |
| <b>Applicable Standards</b>             | cCSAus<br>C22.2 No. 182.1-07                      |
| <b>Accessory Size</b>                   | 3   |
| <b>Base Drawing Number</b>              | <a href="#">35-34xxx-xxx-haz.PDF</a>              |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-zone2-ds30-en.pdf</a> |