



# DS200 HAZ INLET

36-28042-174-HAZ

## SPECIFICATIONS

200 A  
 480 VAC  
 Type 4X

|   |  |
|---|--|
| <b>Rated Current (A)</b>                | 200 A  |
| <b>Rated Voltage (V)</b>                | 480 VAC  |
| <b>Contact Configuration</b>            | 2P+G   |
| <b>Auxiliary Contacts</b>               | +4 AUX   |
| <b>Ratings Information</b>              | NON-CURRENT INTERRUPTING                           |
| <b>Environmental Rating</b>             | Type 4X  |
| <b>Short Circuit Rating</b>             | 10 kA - CLOSE & WITHSTAND                          |
| <b>Impact Rating</b>                    | IK10   |
| <b>Material</b>                         | METAL  |
| <b>Metal Type</b>                       | ZAMAK  |
| <b>Product Color</b>                    | METAL  |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                       |
| <b>Maximum Operating Temperature</b>    | 104F<br>40C  |
| <b>Wiring Capacity - Phase Contacts</b> | 4 AWG – 4/0 AWG<br>SCREW TERMINAL                  |
| <b>Applicable Standards</b>             | cCSAus<br>C22.2 No. 182.1-07                       |
| <b>Accessory Size</b>                   | 6  |
| <b>Base Drawing Number</b>              | <a href="#">36-28xxx-xxx-haz.PDF</a>               |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-zone2-ds200-en.pdf</a> |