



DS200 HAZ INLET

36-28143-972-HAZ

SPECIFICATIONS

200 A
 600 VAC
 Type 4X
 100 hp

| | |
|---|---|
| Rated Current (A) | 200 A |
| Rated Voltage (V) | 600 VAC |
| Horsepower Rating | 100 hp |
| Contact Configuration | 3P+G |
| Auxiliary Contacts | +2 AUX |
| Ratings Information | NON-CURRENT INTERRUPTING BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH |
| Environmental Rating | Type 4X |
| Short Circuit Rating | 10 kA - CLOSE & WITHSTAND |
| Impact Rating | IK10 |
| Material | METAL |
| Metal Type | ZAMAK |
| Product Color | METAL |
| Minimum Operating Temperature | -40F -40C |
| Maximum Operating Temperature | 140F 60C |
| Wiring Capacity - Phase Contacts | 4 AWG – 4/0 AWG SCREW TERMINAL |
| Applicable Standards | cCSAus C22.2 No. 182.1-13 |
| Accessory Size | 6 |
| Base Drawing Number | 36-28xxx-xxx-haz.PDF |
| Catalog | meltric-catalog-zone2-ds200-en.pdf |