



# DS60 HAZ RECEPTACLE

36-64165-HAZ

## SPECIFICATIONS

60 A  
 120 VAC  
 Type 4X  
 3 hp

<b>Rated Current (A)</b>	60 A
<b>Rated Voltage (V)</b>	120 VAC
<b>Horsepower Rating</b>	3 hp
<b>Contact Configuration</b>	1P+N+G
<b>Auxiliary Contacts</b>	NO AUX
<b>Ratings Information</b>	NON-CURRENT INTERRUPTING
<b>Environmental Rating</b>	Type 4X
<b>Short Circuit Rating</b>	100 kA - CLOSE & WITHSTAND
<b>Impact Rating</b>	IK09
<b>Material</b>	METAL
<b>Metal Type</b>	ZAMAK
<b>Product Color</b>	BLACK
<b>Minimum Operating Temperature</b>	-40F -40C
<b>Maximum Operating Temperature</b>	104F 40C
<b>Wiring Capacity - Phase Contacts</b>	10 AWG – 2 AWG SCREW TERMINAL
<b>Hazardous Ratings</b>	Class I Zone IIC Class I Div 2 Groups A,B,C,D T6
<b>Applicable Standards</b>	cCSAus C22.2 No. 182.1-07
<b>Accessory Size</b>	4
<b>Base Drawing Number</b>	<a href="#">36-64xxx-xxx-haz.PDF</a>
<b>Catalog</b>	<a href="#">meltric-catalog-zone2-ds60-en.pdf</a>