



# DS7c RECEPTACLE

37-34561-172-843-NC

## SPECIFICATIONS

30 A

600 VAC/130 VDC

IP66/IP67/IP69

<b>Rated Current (A)</b>	30 A
<b>Rated Voltage (V)</b>	600 VAC/130 VDC
<b>Contact Configuration</b>	6P+G
<b>Auxiliary Contacts</b>	+2 AUX
<b>Ratings Information</b>	CURRENT INTERRUPTING
<b>Environmental Rating</b>	IP 66/67/69
<b>Impact Rating</b>	IK09
<b>Material</b>	METAL
<b>Metal Type</b>	ALUMINUM
<b>Product Color</b>	BLUE
<b>Minimum Operating Temperature</b>	-40F -40C
<b>Maximum Operating Temperature</b>	140F 60C
<b>Wiring Capacity - Phase Contacts</b>	14 AWG – 8 AWG SCREW TERMINAL
<b>Option(1)</b>	PADLOCK PAWL
<b>Option(2)</b>	SELF-RETURNING LID
<b>Accessory Size</b>	4
<b>Base Drawing Number</b>	<a href="#">37-345xx.pdf</a>
<b>Catalog</b>	<a href="#">meltric-catalog-ds7c-dr7c-en.pdf</a>