



DS60 RECEPTACLE

37-64167-375-843

SPECIFICATIONS

60 A

120/208 VAC

Type 4X & IP69

3 hp/10 hp

Rated Current (A)	60 A
Rated Voltage (V)	120/208 VAC
Horsepower Rating	3 hp/10 hp
Contact Configuration	3P+N+G
Auxiliary Contacts	NO AUX
Ratings Information	SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH
Environmental Rating	Type 4X IP 66/67 IP 69
Short Circuit Rating	100 kA - CLOSE & WITHSTAND
Impact Rating	IK09
Material	METAL
Metal Type	ALUMINUM
Product Color	BLUE
Minimum Operating Temperature	-40F -40C
Maximum Operating Temperature	140F 60C
Wiring Capacity - Phase Contacts	10 AWG – 2 AWG SCREW TERMINAL
Applicable Standards	UL 2682 UL 1682 cCSAus C22.2 No. 182.1-13
Option(1)	MUSHROOM PAWL
Option(2)	PADLOCK PAWL
Accessory Size	4
Base Drawing Number	37-64xxx.PDF
Catalog	meltric-catalog-ds60-en.pdf