



# DR250 RECEPTACLE

39-24245-K04

## SPECIFICATIONS

250 A

277 VAC

Type 4X

|                                  |                                              |
|----------------------------------|----------------------------------------------|
| Rated Current (A)                | 250 A                                        |
| Rated Voltage (V)                | 277 VAC                                      |
| Contact Configuration            | 1P+N+G                                       |
| Auxiliary Contacts               | NO AUX                                       |
| Ratings Information              | NON-CURRENT INTERRUPTING                     |
| Environmental Rating             | Type 4X<br>IP 66/67                          |
| Short Circuit Rating             | 10 kA - CLOSE & WITHSTAND                    |
| Impact Rating                    | IK10                                         |
| Material                         | METAL                                        |
| Metal Type                       | ALUMINUM                                     |
| Product Color                    | BLUE                                         |
| Minimum Operating Temperature    | -40F<br>-40C                                 |
| Maximum Operating Temperature    | 140F<br>60C                                  |
| Wiring Capacity - Phase Contacts | 4 AWG – 4/0 AWG<br>SCREW TERMINAL            |
| Applicable Standards             | UL 1682<br>cCSAus<br>C22.2 No. 182.1-13      |
| Accessory Size                   | 6                                            |
| Base Drawing Number              | <a href="#">39-24xxx-kxx.PDF</a>             |
| Catalog                          | <a href="#">meltric-catalog-dr250-en.pdf</a> |