



# DR250 INLET

39-28032-K07

## SPECIFICATIONS

250 A

250 VAC

|   |   |
|---|---|
| <b>Rated Current (A)</b>                | 250 A                                   |
| <b>Rated Voltage (V)</b>                | 250 VAC                                 |
| <b>Contact Configuration</b>            | 2P+G                                    |
| <b>Auxiliary Contacts</b>               | NO AUX                                  |
| <b>Ratings Information</b>              | NON-CURRENT INTERRUPTING                |
| <b>Environmental Rating</b>             | Type 4X<br>IP 66/67                     |
| <b>Short Circuit Rating</b>             | 10 kA - CLOSE & WITHSTAND               |
| <b>Impact Rating</b>                    | IK10                                    |
| <b>Material</b>                         | METAL                                   |
| <b>Metal Type</b>                       | ALUMINUM                                |
| <b>Product Color</b>                    | METAL                                   |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                            |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                             |
| <b>Wiring Capacity - Phase Contacts</b> | 4 AWG – 4/0 AWG<br>SCREW TERMINAL       |
| <b>Applicable Standards</b>             | UL 1682<br>cCSAus<br>C22.2 No. 182.1-13 |
| <b>Accessory Size</b>                   | 6                                       |
| <b>Base Drawing Number</b>              | <a href="#">39-28xxx-kxx.PDF</a>        |