MELTRIC
A COMPANY OF MARECHAL ELECTRIC

# DR100 INLET

## 39-68233-K16

### SPECIFICATIONS

100 A
208 VAC
Type 4X & IP69

| | |
|---|---|
| **Rated Current (A)** | 100 A |
| **Rated Voltage (V)** | 208 VAC |
| **Contact Configuration** | 3P+G |
| **Auxiliary Contacts** | NO AUX |
| **Ratings Information** | CURRENT INTERRUPTING |
| **Environmental Rating** | Type 4X<br>IP 66/67<br>IP 69 |
| **Short Circuit Rating** | 100 kA - CLOSE & WITHSTAND |
| **Impact Rating** | IK09 |
| **Material** | METAL |
| **Metal Type** | ALUMINUM |
| **Product Color** | METAL |
| **Minimum Operating Temperature** | -40F<br>-40C |
| **Maximum Operating Temperature** | 140F<br>60C |
| **Wiring Capacity - Phase Contacts** | 10 AWG – 2 AWG<br>SCREW TERMINAL |
| **Applicable Standards** | UL 1682<br>cCSAus<br>C22.2 No. 182.1-13 |
| **Accessory Size** | 4 |
| **Base Drawing Number** | 39-68xxx-kxx.PDF |
| **Catalog** | meltric-catalog-dr100-en.pdf |