



# SPEX PLUG

## 42-41003-40P

### SPECIFICATIONS

600 A  
 600 VAC  
 IP65/IP66

<b>Rated Current (A)</b>	600 A
<b>Rated Voltage (V)</b>	600 VAC
<b>Contact Configuration</b>	L3
<b>Auxiliary Contacts</b>	+2 AUX
<b>Ratings Information</b>	NON-CURRENT INTERRUPTING
<b>Environmental Rating</b>	IP 65/66
<b>Impact Rating</b>	IK08
<b>Material</b>	POLY
<b>Product Color</b>	BLACK
<b>Thread Size</b>	M40
<b>Minimum Operating Temperature</b>	-4F -20C
<b>Maximum Operating Temperature</b>	140F 60C
<b>Wiring Capacity - Phase Contacts</b>	2/0 AWG – 777 MCM LUG TERMINAL
<b>Hazardous Ratings</b>	Class I Zone I Class I Div 2 Class II Div I
<b>Applicable Standards</b>	cCSAus C22.2 No. 182.1-07
<b>Accessory Size</b>	S
<b>Base Drawing Number</b>	<a href="#">42-4100x-xxP.PDF</a>
<b>Catalog</b>	<a href="#">meltric-catalog-spex-en.pdf</a>