



# PFQ300 INLET

47-38147-48

## SPECIFICATIONS

300 A

347/600 VAC

IP66/IP67

|   |   |
|---|---|
| <b>Rated Current (A)</b>                | 300 A   |
| <b>Rated Voltage (V)</b>                | 347/600 VAC                                   |
| <b>Contact Configuration</b>            | 3P+N+G  |
| <b>Auxiliary Contacts</b>               | +8 AUX  |
| <b>Ratings Information</b>              | NON-CURRENT INTERRUPTING                      |
| <b>Environmental Rating</b>             | IP 66/67                                      |
| <b>Impact Rating</b>                    | IK10  |
| <b>Material</b>                         | METAL   |
| <b>Metal Type</b>                       | ALUMINUM PAINTED                              |
| <b>Product Color</b>                    | GRAY  |
| <b>Minimum Operating Temperature</b>    | -40F<br>-40C                                  |
| <b>Maximum Operating Temperature</b>    | 140F<br>60C                                   |
| <b>Wiring Capacity - Phase Contacts</b> | 2 AWG – 750 MCM<br>LUG TERMINAL               |
| <b>Applicable Standards</b>             | UL 1682<br>CSA<br>C22.2 No. 182.1-13          |
| <b>Option(1)</b>                        | INLET WITH NO CAP (PF)                        |
| <b>Accessory Size</b>                   | F   |
| <b>Base Drawing Number</b>              | <a href="#">47-38xxx.PDF</a>                  |
| <b>Catalog</b>                          | <a href="#">meltric-catalog-pf-pfq-en.pdf</a> |