



# PF400 RECEPTACLE

49-44043-843

## SPECIFICATIONS

400 A

480 VAC

IP66/IP67

<b>Rated Current (A)</b>	400 A
<b>Rated Voltage (V)</b>	480 VAC
<b>Contact Configuration</b>	3P+G
<b>Auxiliary Contacts</b>	+4 AUX
<b>Ratings Information</b>	NON-CURRENT INTERRUPTING
<b>Environmental Rating</b>	IP 66/67
<b>Impact Rating</b>	IK10
<b>Material</b>	METAL
<b>Metal Type</b>	ALUMINUM PAINTED
<b>Product Color</b>	GRAY
<b>Minimum Operating Temperature</b>	-40F -40C
<b>Maximum Operating Temperature</b>	140F 60C
<b>Wiring Capacity - Phase Contacts</b>	2 AWG – 750 MCM LUG TERMINAL
<b>Applicable Standards</b>	UL 1682 CSA C22.2 No. 182.1-13
<b>Option(1)</b>	PADLOCK PAWL
<b>Accessory Size</b>	C
<b>Base Drawing Number</b>	<a href="#">49-44xxx.PDF</a>
<b>Catalog</b>	<a href="#">meltric-catalog-pf-pfq-en.pdf</a>