



DSN20 RECEPTACLE

63-14143-843-NC

SPECIFICATIONS

20 A
 600 VAC
 Type 4X & IP69
 7.5 hp

| | |
|---|---|
| Rated Current (A) | 20 A |
| Rated Voltage (V) | 600 VAC |
| Horsepower Rating | 7.5 hp |
| Contact Configuration | 3P+G |
| Auxiliary Contacts | NO AUX |
| Ratings Information | SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH |
| Environmental Rating | Type 4X IP 66/67 IP 69 |
| Short Circuit Rating | 100 kA - CLOSE & WITHSTAND |
| Impact Rating | IK09 |
| Material | POLY |
| Product Color | BLUE |
| Minimum Operating Temperature | -40F -40C |
| Maximum Operating Temperature | 140F 60C |
| Wiring Capacity - Phase Contacts | 14 AWG – 12 AWG SCREW TERMINAL |
| Applicable Standards | UL 1682 UL 2682 cCSAus C22.2 No. 182.1-13 |
| Option(1) | PADLOCK PAWL |
| Option(2) | SELF-RETURNING LID |
| Accessory Size | 1 |
| Base Drawing Number | 63-14xxx.PDF |
| Catalog | meltric-catalog-dsn20-en.pdf |