



DSN150 RECEPTACLE

63-94143-375-843-NC

SPECIFICATIONS

150 A
 600 VAC
 Type 4X & IP69
 75 hp

Rated Current (A)	150 A
Rated Voltage (V)	600 VAC
Horsepower Rating	75 hp
Contact Configuration	3P+G
Auxiliary Contacts	NO AUX
Ratings Information	SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH
Environmental Rating	Type 4X IP 66/67 IP 69
Short Circuit Rating	100 kA - CLOSE & WITHSTAND
Impact Rating	IK09
Material	POLY
Product Color	BLUE
Minimum Operating Temperature	-40F -40C
Maximum Operating Temperature	140F 60C
Wiring Capacity - Phase Contacts	4 AWG - 2/0 AWG SCREW TERMINAL
Applicable Standards	UL 1682 UL 2682 cCSAus C22.2 No. 94.2-15
Option(1)	PADLOCKABLE MUSHROOM PAWL
Option(2)	SELF-RETURNING LID
Accessory Size	5
Base Drawing Number	63-94xxx.PDF
Catalog	meltric-catalog-dsn150-en.pdf