



# DSN37c RECEPTACLE

63-C4003-375-843-NC

## SPECIFICATIONS

8 A

480 VAC/ VDC

Type 4X & IP69

<b>Rated Current (A)</b>	8 A
<b>Rated Voltage (V)</b>	480 VAC/ VDC
<b>Contact Configuration</b>	36P+G
<b>Ratings Information</b>	NON-CURRENT INTERRUPTING
<b>Environmental Rating</b>	Type 4X IP 69
<b>Impact Rating</b>	IK09
<b>Material</b>	POLY
<b>Product Color</b>	BLUE
<b>Minimum Operating Temperature</b>	-40F -40C
<b>Maximum Operating Temperature</b>	140F 60C
<b>Wiring Capacity - Phase Contacts</b>	18 AWG – 14 AWG SOLDER/CRIMP TERMINAL
<b>Applicable Standards</b>	UL 2238
<b>Option(1)</b>	PADLOCKABLE MUSHROOM PAWL
<b>Option(2)</b>	SELF-RETURNING LID
<b>Accessory Size</b>	3
<b>Base Drawing Number</b>	<a href="#">63-c4003.pdf</a>
<b>Catalog</b>	<a href="#">meltric-catalog-dsn37c-ds37c-en.pdf</a>