



DSN150 RECEPTACLE

67-94042

SPECIFICATIONS

150 A
 480 VAC
 75 hp

| | |
|---|---|
| Rated Current (A) | 150 A |
| Rated Voltage (V) | 480 VAC |
| Horsepower Rating | 75 hp |
| Contact Configuration | 2P+G |
| Auxiliary Contacts | NO AUX |
| Ratings Information | SWITCH RATED BRANCH CIRCUIT DISCONNECT SWITCH MOTOR CIRCUIT DISCONNECT SWITCH |
| Environmental Rating | Type 4X IP 66/67 IP 69 |
| Short Circuit Rating | 100 kA - CLOSE & WITHSTAND |
| Impact Rating | IK10 |
| Material | METAL |
| Metal Type | ALUMINUM |
| Product Color | BLUE |
| Minimum Operating Temperature | -40F -40C |
| Maximum Operating Temperature | 140F 60C |
| Wiring Capacity - Phase Contacts | 4 AWG – 2/0 AWG SCREW TERMINAL |
| Applicable Standards | UL 1682 UL 2682 cCSAus C22.2 No. 94.2-15 |
| Accessory Size | 5 |
| Base Drawing Number | 67-94xxx.pdf |
| Catalog | meltric-catalog-dsn150-en.pdf |