

# DR150 Standard Duty Plugs & Receptacles – 150 A

## UL/CSA Ratings

- **Max Amperage & Voltage**  
150 A, 600 VAC
- **Current Interruption Capability**  
For current interrupting up to 250 VAC  
For Switch-Rated devices, see DS & DSN sections.
- **Short Circuit Rating**  
65kA  
Testing was performed with RK1 current limiting fuses sized at least 100% of the devices ampacity rating.
- **Environmental Ratings**  
Type 4X (Poly Standard)  
Type 3R (Metal Standard)  
Type 4X (Metal Optional)
- **Temperature Range**  
Min -40°F / Max 140°F  
See pg 258 for temps below -15°F.
- **Wiring Capacity**  
Min 4 AWG Max 2/0 AWG  
Aux Contacts - Max 14 AWG  
Based on THHN wire sizes
- **Certifications**  
UL 1682, CSA 182.1

## Receptacle (female)

## Inlet (male)



## North American UL/CSA Configurations

Voltage	Polarity	Part #		Part #	
		Poly	Metal	Poly	Metal
120V	1P+N+G	31-94235-K16	39-94235-K16	31-98235-K16	39-98235-K16
120 208V	3P+N+G	31-94237-K16	39-94237-K16	31-98237-K16	39-98237-K16
125V	1P+N+G	31-94175-K07	39-94175-K07	31-98175-K07	39-98175-K07
125 250V	2P+N+G	31-94176-K07	39-94176-K07	31-98176-K07	39-98176-K07
208V	2P+G	31-94232-K16	39-94232-K16	31-98232-K16	39-98232-K16
208V	3P+G	31-94233-K16	39-94233-K16	31-98233-K16	39-98233-K16
250V	2P+G	31-94172-K07	39-94172-K07	31-98172-K07	39-98172-K07
250V	3P+G	31-94173-K07	39-94173-K07	31-98173-K07	39-98173-K07
277V	1P+N+G	31-94245-K04	39-94245-K04	31-98245-K04	39-98245-K04
277 480V	3P+N+G	31-94247-K04	39-94247-K04	31-98247-K04	39-98247-K04
347 600V	3P+N+G	31-94187-K14	39-94187-K14	31-98187-K14	39-98187-K14
480V	2P+G	31-94242-K04	39-94242-K04	31-98242-K04	39-98242-K04
480V	3P+G	31-94243-K04	39-94243-K04	31-98243-K04	39-98243-K04
600V	2P+G	31-94182-K14	39-94182-K14	31-98182-K14	39-98182-K14
600V	3P+G	31-94183-K14	39-94183-K14	31-98183-K14	39-98183-K14

For international configurations and ratings (IEC, CE) visit [meltric.com/international-catalog](http://meltric.com/international-catalog) or contact customer service at 800-433-7642.

## Main Options



## Receptacle Options

## Suffix #

## Inlet Options

## Suffix #

With 2 Auxiliary/Pilot Contacts	Recept # - 262	With 2 Auxiliary/Pilot Contacts	Inlet # - 262
With 3 Auxiliary/Pilot Contacts	Recept # - 263	With 3 Auxiliary/Pilot Contacts	Inlet # - 263
With 4 Auxiliary/Pilot Contacts	Recept # - 264	With 4 Auxiliary/Pilot Contacts	Inlet # - 264
With 5 Auxiliary/Pilot Contacts	Recept # - 975	With 5 Auxiliary/Pilot Contacts	Inlet # - 975
With 6 Auxiliary/Pilot Contacts	Recept # - 976	With 6 Auxiliary/Pilot Contacts	Inlet # - 976
Type 4X & Closed Lid Configuration	Recept # - 4X <sup>i</sup>	Type 4X Watertightness	Inlet # - 4X <sup>i</sup>
Mushroom Pawl	Recept # - 375	With No Lockout Hole	Inlet # - A155
Padlock Pawl	Recept # - 843	For Auxiliary Switch	Inlet # - NNF*
Padlockable Mushroom Pawl	Recept # - 375-843		
Screw-Type Locking Pawl	Recept # - 845		
Metal Pawl (on poly receptacle)	Recept # - 824		
180° Opening Lid	Recept # - 180++ <sup>i</sup>		
Closed Lid Configuration	Recept # - NC		
With Auxiliary Switch	Recept # - 270+		

Notes: \* Order inlet with P+N+G configuration and receptacle with P+G configuration.  
<sup>i</sup> Metal devices only.

See pages 235-244 for detailed information on these options



Notes: + Not UL/CSA listed.  
++ Required when mating to rigid mounted male inlet.  
<sup>i</sup> Metal devices only.

Order Example: 480V DR150 + 2 auxiliary contacts  
DR150 Poly inlet 3P+G = 31-98243-K04-972

# INSTALLATION ACCESSORIES – SIZE 5


Unless indicated otherwise, accessories can be used with either poly or metal plugs and receptacles.


**HANDLES**

HANDLE w/NPT		Part # Poly	Part # Metal
	3/4"	515P0N07	595P0N07
	1"	515P0N10	595P0N10
	1 1/4"	515P0N12	595P0N12
	1 1/2"	515P0N15	595P0N15
	2"	515P0N20	595P0N20

For metal devices only


For available cord grips, see pg 167.

POLY HANDLE w/CORD GRIP	Cable Range	Part #
	.980 - 1.260"	715P0EP4
	1.260 - 1.560"	715P0FP1
	1.520 - 1.860"	715P0GP2

METAL HANDLE w/CORD GRIP	Cable Range	Part #
	1.250 - 1.375"	795P0FS1
	1.438 - 1.562"	795P0FS2*
	1.562 - 1.688"	795P0FS3*
	1.688 - 1.812"	795P0GS1

For metal devices only

\*May require stripping of cable jacket.

METAL OVERSIZED HANDLE w/NPT	Cable Range	Part #
	3/4"	795P0N07
	1"	795P0N10
	1 1/4"	795P0N12
	1 1/2"	795P0N15
	2"	795P0N20

For metal devices only


2 1/2"

795P0N25



For available cord grips, see pg 167.

SANTOPRENE HANDLE		
	.70 - 1.000"	555P0D25
	.984 - 1.377"	555P0D35
	1.378 - 1.771"	555P0D45

IP66/IP67


POLY HANDLE w/CLAMP & BUSHING	Cable Range	Part #
	1.250 - 1.375"	715P0S22
	1.438 - 1.562"	715P0S25
	1.562 - 1.688"	715P0S27
	1.688 - 1.812"	715P0S29

**ANGLES**

POLY ANGLE		
	30°	515M3
METAL ANGLE		
	0°	595M0
	30°	595M3
	Oversized 30°	795M3
	70°	595M7


Mounts on oversize metal box only. Order with 7T6F0N25XL. See pg 52.

**BOXES**

POLY ANGLE WITH METAL BOX w/NPT				Part #
	30°	1 1/4"		715C3N12
	30°	1 1/2"		715C3N15
	30°	2"		715C3N20
	30°	2 1/2"		715C3N25

\* 108.7 in<sup>3</sup>

\* Interior volume with receptacle installed.

METAL ANGLE WITH METAL BOX w/NPT				Part #
	30°	1 1/4"		795C3N12
	30°	1 1/2"		795C3N15
	30°	2"		795C3N20
	30°	2 1/2"		795C3N25

\* 111.8 in<sup>3</sup>

\* Interior volume with receptacle installed.


METAL BOX w/NPT			
	0°	1 1/4"	7T5F0N12
	0°	1 1/2"	7T5F0N15
	0°	2"	7T5F0N20
	0°	2 1/2"	7T5F0N25

NPT on top or bottom (if rotated). For other NPT configurations, contact customer service.

**MISCELLANEOUS ACCESSORIES**

PROTECTIVE INLET/PLUG CAP		
	31-9A426	For Inlets/Plugs Only. Covers lockout hole for watertight seal on inlet. Consult Customer Service for availability.

PADLOCKABLE INLET/PLUG CAP		
	DS9MC	Aluminum – For Inlets/Plugs Only. -A155 suffix required to maintain water ingress protection.

CORD GRIP with MESH		
	see pg 167	

EASY RETROFIT ADAPTER PLATES		
	see pg 164	Mount to existing boxes.

RECEPTACLE LOCKING PIN		
	LP-843	Requires Padlockable Pawl option (-843) on receptacle.