

# DS20 Switch-Rated Plugs & Receptacles – 20 A

## UL/CSA Ratings

- Max Amperage & Voltage**  
20 A, 600 VAC
- Switch-Rating (AC Only)**  
Branch Circuit & Motor Circuit Disconnect Switching
- Horsepower Ratings**

120V	1Ø	.75 hp
208V	3Ø	3 hp
240V	3Ø	5 hp
480V	3Ø	7.5 hp
600V	3Ø	10 hp
- Short Circuit Rating**  
100kA Close & Withstand  
Tested with RK1 current limiting fuses sized at 400% of the highest full load motor ampacity.
- Environmental Ratings**  
Type 3R (Standard)  
Type 4X (Optional)
- Temperature Range**  
Min -40°F/Max 140°F  
See pg 258 for temps below -15°F.
- Wiring Capacity**  
Min 14 AWG Max 8 AWG  
Aux Contact - Max 14 AWG  
Based on THHN wire sizes
- Certifications**  
UL 2682, UL 1682, CSA 182.1

## Receptacle (female)



## Inlet (male)



**!** Don't forget to add installation accessories to your order

## North American UL/CSA Configurations

Voltage	Polarity	Part # Poly	Part # Poly
120V	1P+N+G	33-14165	33-18165
120 208V	3P+N+G	33-14167	33-18167
125V	1P+N+G	33-14075	33-18075
125 250V	2P+N+G	33-14076	33-18076
208V	2P+G	33-14162	33-18162
208V	3P+G	33-14163	33-18163
250V	2P+G	33-14072	33-18072
250V	3P+G	33-14073	33-18073
277V	1P+N+G	33-14045	33-18045
277 480V	3P+N+G	33-14047	33-18047
347 600V	3P+N+G	33-14147	33-18147
480V	2P+G	33-14042	33-18042
480V	3P+G	33-14043	33-18043
600V	2P+G	33-14142	33-18142
600V	3P+G	33-14143	33-18143

For international configurations and ratings (IEC,CE) visit [meltric.com/international-catalog](http://meltric.com/international-catalog) or contact customer service at 800-433-7642.

## Main Options



**Auxiliary/Pilot Contacts**



**Mushroom Pawl**



**Padlock Pawl**



**Closed Lid Configuration**  
Recommended for cord applications to keep lid tucked in to avoid damage.

## Receptacle Options

## Suffix #

## Inlet Options

## Suffix #

With 2 Auxiliary/Pilot Contacts	<b>Recept # - 972</b>	With 2 Auxiliary/Pilot Contacts	<b>Inlet # - 972</b>
Type 4X & Closed Lid Configuration	<b>Recept # - 4X</b>	Type 4X Watertightness	<b>Inlet # - 4X</b>
Straight Insertion	<b>Recept # - 352</b>	Self-Ejecting Plug Release	<b>Inlet # - 338</b>
Self-Ejecting Connector Release	<b>Recept # - 354</b>	With No Lockout Hole	<b>Inlet # - A155</b>
Mushroom Pawl	<b>Recept # - 375</b>	For Auxiliary Switch	<b>Inlet # - NNF*</b>
Padlock Pawl	<b>Recept # - 843</b>		
Padlockable Mushroom Pawl	<b>Recept # - 375-843</b>		
Screw-Type Locking Pawl	<b>Recept # - 845</b>		
Metal Pawl (on Poly Receptacle)	<b>Recept # - 824</b>		
Closed Lid Configuration	<b>Recept # - NC</b>		
With Auxiliary Switch	<b>Recept # - 270+</b>		

**Notes:** \* Order inlet with P+N+G configuration and receptacle with P+G configuration.

**Notes:** + Not UL/CSA listed.


**!** See pages 235-244 for detailed information on these options

**Order Example: 208V DS20 + 2 auxiliary contacts**  
DS20 Poly inlet 2P+G = 33-18162-972


# INSTALLATION ACCESSORIES – SIZE 2


Unless indicated otherwise, accessories can be used with either poly or metal plugs and receptacles.

**HANDLES**


HANDLE w/NPT	Part # Poly	Part # Metal
 Poly 1/2"	512P0N05	592P0N05
3/4"	512P0N07	592P0N07
1"	512P0N10	592P0N10
1 1/4"	512P0N12	-

For available cord grips, see page 167.


POLY HANDLE w/CORD GRIP	Cable Range	Part #
	.350 - .520"	712P0BP6
	.520 - .680"	712P0CP5
	.680 - .980"	712P0DP4
	.980 - 1.260"	712P0EP4

METAL HANDLE w/CORD GRIP	Cable Range	Part #
	.438 - .500"	792P0BS3
	.500 - .562"	792P0BS4
	.562 - .625"	792P0CS2
	.625 - .750"	792P0CS4
	.750 - .875"	792P0DS1
	.875 - 1.000"	792P0DS3


POLY HANDLE	Cable Range	Part #
	.20 - .83"	512P0D21


POLY HANDLE w/CLAMP & BUSHING	Cable Range	Part #
	.750 - .875"	712P0S14
	.875 - 1.000"	712P0S16
	1.000 - 1.125"	712P0S18
	1.125 - 1.250"	712P0S20
	1.250 - 1.375"	712P0S22


**ANGLES**

POLY ANGLE	Angle	Part #	Notes
	30°	512M3	

POLY ANGLE	Angle	Part #	Notes
	70°	512M7	Panel mounting only.



METAL ANGLE	Angle	Part #
	0°	592M0


METAL ANGLE	Angle	Part #
	30°	592M3


METAL ANGLE	Angle	Part #	Notes
	FS/FD Box 30°	792M3FS	* Base measures approximately 4.2" x 2.7". Due to the variation in sizes of FS boxes, please verify that your FS box matches our dimensions, if not call Customer Service for other solutions.


**BOXES**

POLY CONDUIT ENTRY w/NPT	Angle	Size	Part #	Notes
	30°	1/2"	512B3N05	For poly devices only
	30°	3/4"	512B3N07	* Interior volume with receptacle installed.

POLY WALL BOX w/ANGLE	Angle	Part #	Notes
	70°	512C7000	70° poly boxes are not drilled. Contact Customer Service if factory drilling is required.
	Ground Bar	51AA089	* Interior volume with receptacle installed.


POLY ANGLE WITH METAL BOX w/NPT	Angle	Size	Part #	Notes
	70°	1/2"	712C7N05	
	70°	3/4"	712C7N07	
	70°	1"	712C7N10	* Interior volume with receptacle installed.
	70°	1 1/4"	712C7N12	
	70°	1 1/2"	712C7N15	

METAL BOX w/NPT	Angle	Size	Part #
	0°	1/2"	7T1F0N05
	0°	3/4"	7T1F0N07
	0°	1"	7T1F0N10
	0°	1 1/4"	7T1F0N12

POLY ANGLE WITH METAL BOX w/NPT	Angle	Size	Part #	Notes
	30°	1/2"	712C3N05	
	30°	3/4"	712C3N07	* Interior volume with receptacle installed.
	30°	1"	712C3N10	
	30°	1 1/4"	712C3N12	


NPT on top or bottom (if rotated). For other NPT configurations, contact Customer Service.


**MISCELLANEOUS ACCESSORIES**


FINGER DRAWPLATES	Part #	Notes
	61-3A346	Set of Two (2) Recommended for cord to cord assembly applications, for easier connector closure.

PROTECTIVE INLET/PLUG CAP	Part #	Notes
	31-1A426	For Inlets/Plugs Only.

PADLOCKABLE INLET/PLUG CAP	Part #	Notes
	DS1PC	For Inlets/Plugs Only.

SPRING-LOADED PADLOCKABLE INLET/PLUG CAP	Part #	Notes
	31-1A226	For Inlets/Plugs Only. -A155 suffix required to maintain water ingress protection.

EASY RETROFIT ADAPTER PLATES	Part #	Notes
	see pg 164	Mount to existing boxes.

RECEPTACLE LOCKING PIN	Part #	Notes
	LP-843	Requires Padlockable Pawl option (-843) on receptacle.